

NSP1-50-275-N



Image for illustrative purposes only

NSP Surge Diverter

The NSP1-50-275-N provides all mode protection (L-N and N-PE) in accordance with AS3000 for single phase sub-boards remote from the MSB. It is rated for both 8/20 μ s and 10/350 μ s impulses making it suitable for use in moderately high exposure locations, for example in a sub-board fed by overhead conductors. It is also suitable for main switchboard protection in non-MEN (TT) distribution systems.

Pluggable Top

The Novaris NSP range features pluggable modules, colour coded orange for L-N and black for N-PE, where applicable.


Display and Alarm

The NSP range features a display window with green indicating operational and red indicating that replacement is necessary. A voltage free changeover contact allows for external alarm indication.


Overcurrent Protection

The NSP range requires external overcurrent protection as detailed in AS3000. Novaris surge circuit breakers (SCB) are recommended for this. The overcurrent protection function can also be provided by a conventional circuit breaker or fuses. Alternatively, the NSP can be paralleled with an existing power circuit. The NSP draws negligible current under normal conditions so it will not affect the circuit current loading.

Wiring







Dimensions



Product Datasheet

Electrical Specifications

Connection type		Shunt
Modes of protection		L-N, N-PE
Number of ports		1
Number of phases		1
Location		Indoor
Nominal voltage	U_0	230VAC
Short circuit withstand level	I_{SCCR}	25kA
Maximum backup fuse or CB		32A
Recommended SCB		SCB1-3-80

Electrical (L-N) Specifications

Maximum continuous voltage AC	U_c	275VAC
Maximum discharge current (8/20 μ s)	I_{max}	50kA
Nominal discharge current (8/20 μ s)	I_n	20kA
Lightning impulse current (10/350 μ s)	I_{imp}	7.5kA
Voltage protection level (I_n)	U_p	<1200V
Response time	t_A	<25ns












Electrical (N-PE) Specifications

Maximum continuous voltage	U_c	255VAC
Maximum discharge current (8/20 μ s)	I_{max}	50kA
Nominal discharge current (8/20 μ s)	I_n	20kA
Lightning impulse current (10/350 μ s)	I_{imp}	12.5kA
Voltage protection level (1kV/ μ s)	U_p	<1500V
Response time	t_A	<100ns
Follow current interrupt rating	I_{fi}	100A

Indication Specifications

Display		Thermal failure green normal red failure
---------	---	--


Mechanical Specifications

Minimum operating temperature		-40°C
Maximum operating temperature		80°C
Minimum operating humidity		5%
Maximum operating humidity		95%
Mounting method		TS35 DIN Rail
Environmental rating		IP20
Terminal capacity - power		35mm ²
Terminal capacity - alarms		1.5mm ²
Length		99mm
Width		36mm
Height		67mm

Standard Specifications

IEC 61643-11	
AS 1768	LPZ0B/1, LPZ1/2
AS3000	

Other Specifications

Product Code		NSP1-50-275-N
--------------	---	---------------

Shipping Specifications

Weight		210g
Customs tariff		85363000, 85363010